



## Dodge Neon 2.0L Oil Pan P/N 20800

### Installation Instructions

**These instructions are a basic guideline and some descriptions may not apply to all vehicles. Always consult the proper Service Manual for complete instructions.**

Make sure vehicle is in Park and on a level surface, emergency brake on, chock wheels and jack up vehicle, use approved jack stands for safety. Or, put car safely on a lift.

Drain oil from pan and remove oil pan from engine. Consult the proper service manual for complete disassembly instructions.

Clean any old gasket material from engine block and sealing areas.

Thoroughly clean the inside of your new Moroso Oil Pan. This means also removing the Windage Tray. Inspect all pieces for any debris or protective vinyl coverings that may have been left on.

Re-install the Windage Tray and tighten securely.

Install a new factory quality oil pan gasket to the oil pan rail using a light coating of RTV silicone to hold the gasket firmly in place.

Install the oil pan, **DO NOT USE FORCE**. Secure to engine with factory hardware and tighten in an X-pattern starting from the center outwards. Torque these to 108 in. lbs., (9 ft. lbs.).

Reinstall any parts removed during oil pan removal, following service manual instructions. Make any necessary modifications or adjustments to interfering parts.

The upper 1/2" NPT Bung is for a turbo drain and the lower 1/2" NPT Bung is used for an oil temperature sender. It is recommended that a -10AN line be used for a turbo drain line. If any of these fittings are not being used, they should be blocked off with the provided plugs and a Teflon pipe sealant.

Place washer onto magnetic drain plug and install. Do not over tighten.

Refill with fresh oil to full line on dipstick and check for leaks. The factory dipstick can still be used to check the oil level. The Moroso Oil Pan holds 6.25 quarts of oil, not including the oil filter. Run engine for 5-minutes and re-check oil level.

For Technical Assistance, call Moroso's Tech Line at  
(203) 458-0542, (203) 458 0546 8:30am-5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC  
80 CARTER DR • GUILFORD, CT 06437  
Phone: (203) 453-6571 • Fax: (203) 453-6906