



**INSTRUCTIONS**  
**ALL WEATHER SEAL**  
**(1 Pint)**  
**P/N 35520**

**CAUTION:** Never remove radiator cap when engine is hot and under pressure. Open petcock slowly to relieve pressure, and then close. Then, take off radiator cap.

In an emergency, when the system cannot be drained. Moroso All Weather Seal can be put into a cooling system which contains anti-freeze/coolant, but for best results the cooling system should be thoroughly cleaned with a cooling system flush, and refilled with clear water before adding Moroso All Weather Seal. Dispose of old anti-freeze/coolant properly, according to your state's environmental regulations. Use one pint bottle for passenger cars and small trucks. For larger cooling systems use one bottle for each six gallons of water capacity.

1. **SHAKE BOTTLE WELL AND WITH ENGINE RUNNING AT NORMAL OPERATING TEMPERATURE, POUR ALL WEATHER SEAL INTO RADIATOR . WASH THE RADIATOR OPENING AND REPLACE THE CAP.**
2. Run the engine until leak stops (usually two to five minutes).
3. If necessary, anti-freeze may be added to the mixture of water and All Weather Seal, **but under no circumstances should All Weather Seal be left in a cooling system for more than twenty-four hours.**
4. Before the twenty-four hour period has elapsed , the cooling system should be drained and flushed, as follows:
  - Open petcock and start to drain system. Remove radiator cap.
  - Add water to keep radiator full with petcock draining.
  - Start engine and allow to drain until water runs clear. Again, dispose of old anti-freeze/coolant properly according to your state's environmental regulations.
5. Close petcock and refill with clear water and anti-freeze/coolant.

If Moroso All Weather Seal does not stop the leak, it is very likely that no chemical sealer will work and a mechanical repair will be necessary.

**CAUTION**

Avoid contact with eyes and skin. Do not take internally. If splashed on skin, wash off with cool water. If splashed in eyes, flush thoroughly for 15 minutes with cool water. Consult a physician. If taken internally, give 3 or 4 glasses of water or milk. **DO NOT** induce vomiting. Call a physician immediately.

**For Technical Assistance, Call Moroso's Tech Line at  
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC  
80 CARTER DR • GUILFORD, CT 06437-2116  
Phone: (203) 453-6571 • Fax: (203) 453-6906